

DC FAN NOMENCLATURE GUIDE, RC BLOWER

GUIDE ONLY. ALL COMBINATIONS MAY NOT BE DESIGNED OR AVAILABLE

<u>PRODUCT NAME</u> _____	XX	XX	X	X	X	X	X
RC = 7.5 IN BLOWER BOX	_____	_____	_____	_____	_____	_____	_____
<u>NOMINAL VOLTAGE</u> _____	_____	_____	_____	_____	_____	_____	_____
12 = 12 VDC NOMINAL	_____	_____	_____	_____	_____	_____	_____
24 = 24 VDC NOMINAL	_____	_____	_____	_____	_____	_____	_____
48 = 48 VDC NOMINAL	_____	_____	_____	_____	_____	_____	_____
<u>MAJOR ELECTROMECHANICAL VARIATIONS</u> _____	_____	_____	_____	_____	_____	_____	_____
B = FULL SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
C = 7/8 SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
F = 1/2 SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
H = 3/4 SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
K = HIGH SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
M = 5/8 SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
R = PROGRAMMABLE (TPV), BALL BEARING	_____	_____	_____	_____	_____	_____	_____
S = THERMAL SPEED CONTROL (TPV), BALL BEARING	_____	_____	_____	_____	_____	_____	_____
Z = EXTRA-HIGH SPEED, BALL BEARING	_____	_____	_____	_____	_____	_____	_____
<u>TPV DESCRIPTION</u> _____	_____	_____	_____	_____	_____	_____	_____
P = PROG, SPCL SPEED	_____	_____	_____	_____	_____	_____	_____
S = TSC, SPCL SPEED	_____	_____	_____	_____	_____	_____	_____
<u>F P S OUTPUT TYPE (STD, ISOLATED)</u> _____	_____	_____	_____	_____	_____	_____	_____
B = BIPOLAR	_____	_____	_____	_____	_____	_____	_____
G = GO NO GO	_____	_____	_____	_____	_____	_____	_____
N = INVERTED OPEN COLLECTOR	_____	_____	_____	_____	_____	_____	_____
Q = OPEN COLLECTOR	_____	_____	_____	_____	_____	_____	_____
R = INVERTED TTL COMPATIBLE, 5V OUT	_____	_____	_____	_____	_____	_____	_____
T = TTL COMPATIBLE, 5 V OUT	_____	_____	_____	_____	_____	_____	_____
X = SPECIAL	_____	_____	_____	_____	_____	_____	_____
<u>F P S DELAY FUNCTION</u> _____	_____	_____	_____	_____	_____	_____	_____
D = 10 ± 4 SECOND DELAY	_____	_____	_____	_____	_____	_____	_____
N = NO DELAY	_____	_____	_____	_____	_____	_____	_____
X = SPECIAL	_____	_____	_____	_____	_____	_____	_____
<u>F P S LATCH FUNCTION</u> _____	_____	_____	_____	_____	_____	_____	_____
L = LATCH	_____	_____	_____	_____	_____	_____	_____
N = NO LATCH	_____	_____	_____	_____	_____	_____	_____
X = SPECIAL	_____	_____	_____	_____	_____	_____	_____
<u>NON-STANDARD</u> _____	_____	_____	_____	_____	_____	_____	_____
X = MINOR E/M VARIATIONS, LEAD LENGTH, MOUNTING, ETC., NOT AFFECTING BASIC FAN PERFORMANCE.	_____	_____	_____	_____	_____	_____	_____

Originator: <i>M. Nulman</i>	Date: <i>1-11-00</i>	Approval: <i>[Signature]</i>	Date: <i>1/11/00</i>
------------------------------	----------------------	------------------------------	----------------------