



AC NOMENCLATURE GUIDE, 47 FR  
MAJOR / PATRIOT, FALCON / MALTESE

GUIDE ONLY. ALL COMBINATIONS MAY NOT BE DESIGNED OR AVAILABLE.

<b>PRODUCT NAME</b>	_____	<b>XX</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>
MR = MAJOR									
PT = PATRIOT									
FA = FALCON									
MA = MALTESE									
		<i>ML = MAJOR (LOW NOISE)</i>							
		<i>PL = PATRIOT (LOW NOISE)</i>							
<b>ELECTRIC CODE</b>	_____								
-2 = 115 V		50/60 Hz							
-5 = 230 V		60 Hz							
-40 = 208 V		400 Hz							
-64 = 45 V	<input type="checkbox"/> W	60Hz							
-77 = 220/230 V		50/60 Hz							
<b>BEARING / POLES</b>	_____								
-A = SLEEVE	2 POLE								
-B = BALL	2 POLE (FULL SPEED)								
-C = SLEEVE	4 POLE								
-D = BALL	4 POLE (HALF SPEED)								
-F = BALL	.875 STACK, SPECIAL PROPELLER								
-H = BALL	HI RELIABILITY								
-K = BALL	12 POLE, 400 Hz								
<b>TERMINATION</b>	_____								
-2 = .187 TERMINALS, THERMAL PROTECTION, CAPACITOR									
-3 = .110 TERMIANLS, THERMAL PROTECTION, CAPACITOR									
-4 = .187 TERMINALS, CAPACITOR									
-5 = .110 TERMINALS, CAPACITOR									
-6 = LEADS (12"), THERMAL PROTECTION, CAPACITOR									
-7 = LEADS (12")									
<b>FPS OUTPUT FUNCTION</b>	_____								
-Q = OPEN COLLECTOR; HI ON PASS, LOW ON FAIL									
-N = INVERTED OPEN COLLECTOR; HI ON FAIL, LOW ON PASS									
-T = TTL COMPATIBLE; HI ON PASS, LOW ON FAIL									
-R = INVERTED TTL COMPATIBLE; HI ON FAIL, LOW ON PASS									
-X = SPECIAL									
<b>FPS DELAY FUNCTION</b>	_____								
-N = NO DELAY									
-D = 10 ±4 SECOND DELAY									
-X = SPECIAL									
<b>FPS LATCH FUNCTION</b>	_____								
-N = NO LATCH									
-L = LATCH									
-X = SPECIAL									
<b>NON-STANDARD</b>	_____								

X = E/M VARIATIONS / FEATURES, INCLUDING MOUNTING, TERMINATION (HARNESS), LEAD LENGTH, ETC., NOT SAFETY RELEVANT.